

EFFISUS COAT NP PRIMER

DESCRIPTION

Effisus Coat NP Primer is a ready-to-use sub-coat for absorbent building surfaces. It serves as a bonding agent for the subsequent adhesion of Effisus Ecofacace waterproof façade sealing systems.

TECHNICAL DATA

Use

As a bonding agent when applying Effisus Ecofacade SA-Edge sealing membranes.

As a bonding agent when using Effisus Contact Adhesive and Effisus Bonding KT and Effisus Bonding KF, if adhering to moist, absorbent structures or at temperatures down to -10°C.

Please note

If sealing is carried out at low temperatures, make absolutely sure that the substructure will not be covered with a layer of ice!

Application

Stir primer well before use. Apply a thin, even coat with brush or roller.

Allow to ventilate for 5-15 minutes depending on the weather conditions. Upon finger contact with the primed surface, no threads of primer should adhere to your finger (it is preferable to wait a little longer). Subsequently, the next joint can be sealed. The primed surface may remain exposed to the air for several hours before bonding. It should, however, be ensured that no dirt or moisture affects the primed surface. The subsequent bonding must be carried out in line with the respective application guidelines – Effisus Bonding KT Adhesive or Effisus Bonding KF Adhesive.

Yield

Depending on the surface approx. 10g/metre run with an application width of 5cm.

Storage

Store in a cool, frost-free and dry place; away from heat and fire. Keep container tightly closed.

Please note

Effisus Primer contains solvents. When handling, ensure there is a sufficient supply of fresh air. Keep away from fire. Do not smoke.

Accompanying Document

Revision 06/2010

Version

V 1.2 – AT – 30/08/2011