

EFFISUS ADJOIN TI TAPE

DESCRIPTION

Flexible multi-purpose adhesive tape for airtight bonds.

Effisus Adjoin TI Tape is a flexible multi-purpose adhesive tape for airtight bonds indoors and outdoors in accordance with DIN 4108, SAI 180 and ÖNorm B8110-2.

TECHNICAL DATA

Technical data	
Property	Details
Material	Acrylate which is free of solvents or softeners
Temperature resistance	-40°C to 90°C
Roll width	6 centimeters
Roll length	30 meters
3rd party accreditation	IAB
Life expectancy	60 years+
Usage	Interior & Exterior

OTHERS

Effisus Adjoin TI Tape is used to form a secure and permanent seal of overlaps between foil and fleece membranes (vapor checks and airtightness membranes, roof underlays and wall membranes) and joints between such membranes and smooth, non-mineral surfaces.

Effisus Adjoin TI Tape is also suitable for sealing butt joints between wood-based panels such as OSB or MDF sub-roof panels or woodfibres softboards (e.g., Gutex).

Bonds overlaps between sheets of vapour check and joints between wood based panels (such as OSB) also seals service penetrations. Suitable for windows, doors, planed timber, corners and roof windows.

Offers high protection against piercing in corners due to its high elasticity.

With release paper.

Easy to tear by hand.

Related products

Effisus Breather Membrane

Effisus Bonding OF Adhesive

Version

V 1.3 – AT – 15/05/2013