

## Double-sided butyl sealing tape

The Effisus2 Bond GO tape is the innovative solution for day-to-day building or rehabilitations works. The solution's high performance and added value are guaranteed, not only, due to its strict quality control process, but also, due to its high quality constituents, free of harmful substances, such as solvents, chlorine, heavy metals and others. The solution's post production quality is assured by its silicon-based film coating.

It promotes the protection of constructive materials, towards condensation and leaks, whilst also improving the energy efficiency of systems and solutions. It adheres perfectly to vapour barriers, weatherproofing membranes, and most remaining construction materials.

# Effisus 2Bond GO

### Effisus 2Bond GO Tape:

- Exceptional adhesiveness
- Increased ageing resistance
- Service temperatures from -30°C e +80°C
- No need for extra accessories
- Standard widths from 10mm to 50mm
- Thermal and structural vibration-proof

### Typical Applications:

- Sealing overlaps in weatherproofing membranes or vapour barriers
- Sealing joints and perimeter connections of vapour barriers and weatherproofing membranes
- Sealing connections between insulation boards
- Sealing connections between two surfaces
- Sealing perforations / penetrations
- Repairs

### Exceptional adhesion to the following materials:



### SOLUTION BENEFITS

- Robust – 100% waterproof, UV resistant and excellent adhesiveness
- Universal – Different widths for different needs
- Durable – High life-expectancy
- Flexible – Adapts to on-site demands.
- Easy to apply – Simple to handle materials and no need for accessories

### SUPPLY INFORMATION

- Effisus 2Bond GO – 30m rolls with widths between 10mm and 50mm. Other dimensions available upon request.