

Facade waterproofing system with superior fire resistance

Effisus Ecofacade Braze is the innovative system for waterproofing façades in projects with high requirements for fire-action resistance. The system's high performance and added value are guaranteed, not only due to its temperature range resistance, but also to its possibility of full customisation. Through this, application's ease and speed are increased, the possibility of errors during installation are reduced and waste materials are minimized.

The system protects buildings' facade connections from the action of atmospheric agents and potential fire hazards. It ensures both water and air tightness, whilst also maximizing energy efficiency and acoustics.

Effisus Ecofacade Braze

Effisus Ecofacade Braze:

- Fully customisable widths
- Expectable durability of 50 years
- Resistant to UVs and ozone
- Service temperatures from -30°C e +140°C
- Permanently elastic
- Possibility of integrated self-adhesive bands or fast connect gaskets for no need of extra accessories
- Elongation of up to 300%
- Both thermal and structural vibration resistance

Typical Applications:

- Connections in ventilated facades
- Connections in curtain walls
- Connections in traditional facades
- Connections in pre-fabricated facades
- Sustainable construction projects



SOLUTION BENEFITS

- Robust – 100% waterproof, high fire resistance, and UV resistant
- Universal – Customisable dimensions
- Durable – High life-expectancy
- Flexible – Option for integrated self-adhesive bands and/or fast-connect gaskets
- Easy to apply – Simple to handle materials and no need for accessories

SUPPLY INFORMATION

- Effisus Ecofacade Braze – 20m rolls with widths between 10mm and 1320mm. Other dimensions available upon request.