

EFFISUS BONDING KF+P ADHESIVE

DESCRIPTION

Effisus Bonding KF+P Adhesive is a single component adhesive / sealant based on PDMS polymer, solvent-free, for bonding / sealing EPDM and butyl to concrete, masonry, wood, glass, aluminium, steel and bitumen or lap joint connections.

TECHNICAL DATA

Technical characteristics	
Base	PDMS polymer
Colour	Black
Viscosity	Pasty
Density	1.2 g/cm ³
Skin formation	25min

OTHERS

Processing temperature

-5°C to +35°C (surface temperature)
Do not use with temperatures below -5°C.
Do not seal on wet or frozen ground.

Preparation

The surfaces must be dry, clean and free of dust and grease. Pretreatment may be recommended.
Effisus Bonding KF+P Adhesive can be apply with hand or air gun or using a spatula.
Insert the EPDM or butyl material to adhere/ seal immediately, after 10 minutes at the latest and press.
The exact waiting time depends on room temperature, film thickness and absorbency of the substrate.
Due to the different compositions and qualities of foils, preliminary tests are recommended.

Cleaning

Effisus Setup PR Cleaner.

Storage

Store in original containers, at temperatures between +15°C and +35°C and not for more than 12 months.

Safety

Please notice the indications on safety-data-sheet and the safety-indications on the labels of each product for the treatment of our products. Especially the directions of the Dangerous Substance Regulation have to be respected.
Keep the safety-data-sheet of the product you treat ready to hand. It gives you valuable indications for the safe usage, disposal and in case of accidents.

Packaging

310ml Cartridge (Carton of 12 pieces)
600ml Sausage (Carton of 12 pieces)

Accompanying Document

Edition 01/2012

Version

V 1.2 – AP – 09/05/2016 1/1