

ProFlex FR

Elongation Fire rated

Elongation

+ 3x =Layers

5x Futureproof





Effisus ProFlex FR

Interface solution - Fire Rated Weatherproofing Membrane

Effisus ProFlex FR is a watertight, airtight and vapour barrier, fire rated Class B-s3,d0 membrane with a high elongation capacity.

It was designed for sealing façade interfaces and construction joints on typical curtain walls, rainscreen/brick ventilated facades, precast, masonry and many other applications.









Effisus ProFlex FR System



Main Features:

- Watertight: Class W1 Highest classification as per BS EN 1928;
- Fire Performance: B-s3, d0 according to BS EN 13501 1 in conformity with The Building Regulations 2010 Approved Document B (ABD) updated June 2022;
- Excellent Mechanical Properties:
 - 200% Elongation capacity according to BS EN 12311-1, allowing to accommodate building differential movements;
 - Exceptional Tensile & Tear strength as per BS EN12311-1 and BS EN 12310-1;
- Sustainability Environmentally friendly & Recyclable;
- Complete System wide range of fixing/sealing accessories with all compatibilities ensured in accordance with UK end use applications;
- Customization wide range of self-adhesive bands and bespoke layout;
- Unlimited widths.

Testing:





EN 13859-2 BS EN 13859-2

Mass per unit area	EN 1849-2
Thickness	EN 1849-2
Resistance to water penetration	Method A of EN 1928
Water vapour transmission properties	EN ISO 12572
Tensile Properties	EN 12311-1
Tearing Resistance	EN 12310-1
Reaction to Fire	EN 13501-1
SBI (single burning item test)	EN 13823
Ignitability test	EN ISO 11925-2
Artificial ageing acoording to Annex C	EN 1297 EN 1296



proflexfr@effisus.com



Find out more