

Effisus Alltitegutter

The Effisus **Alltitegutter** Membrane is a two-ply EPDM membrane, scrim-reinforced with glassfiber. The product is laminated with a self-adhesive backing, covered by a protective foil. The range of use is as waterproofing membrane for gutter waterproofing.



Effisus Alltitegutter

Technical data

Essential characteristics	Method	Result
Thickness	-	1,6mm
Roll length	-	10lm
Standard roll widths	-	600, 1000, 1600mm
Reaction to fire	EN 13501-1	Class E
Watertightness	EN 1928 B	Pass 24h/60 KPa
Tear resistance	EN 12310-1	Cross direction 150N Length direction 150N
Shear strength of joint	EN 12317-2	200 N/50mm
Peel strength of joint	EN 12316-2	50 N/50mm
Impact resistance	EN 12691 A/B	250mm (A), 1000mm (B)
Tensile strength, length direction	EN 12311-1	600 N/50mm
Tensile strength, cross direction	EN 12311-1	600 N/50mm
Resistance to static loading	EN 12730 (Method B) ^{a)}	≥ 20 kg
Durability watertightness after artificial ageing	EN 1296 EN 1928 ^{b)}	Pass
Durability watertightness against chemicals	EN 1847 EN 1928B ^{c)}	Pass
Dangerous substances	-	No dangerous substances
Weight (1.6mm)	-	1.9kg/m2
Sd value	-	98m

^{a)}
Method B, 24h/20kg

^{b)}
EN 1296 (12 weeks) | EN 1928
(24h/60kPa)

^{c)}
EN 1847 (28d/23°C) | EN 1928B
(24h/60kPa)

Certifications

CE: EN 13967 - Flexible sheets for waterproofing - Plastic and rubber damp proof sheets including plastic and rubber basement tanking sheet.

CE: EN 14909 - Flexible sheets for waterproofing. Plastic and rubber damp proof courses.

CE: EN 13984 - Flexible sheets for waterproofing. Plastic and rubber vapour control layer.

Others

Storage

Store vertically, cool and dry in the original packaging. Store away from combustion sources and open flames. The shelf life is 12 months in unopened packaging.